

Models	
HRT-3MM (Stainless Steel)	Max Wire Rope Diameter: 20mm or .79" Line Tension Capacity: 0-13,000lbs
RL - 1020 K (Standard) RL - 1020 K - SS (Stainless Steel)	Max Wire Rope Diameter: 1.25" Line Tension Capacity: 20 Kips
RL - 1040 K RL - 1040 K SS (Stainless Steel)	Max Wire Rope Diameter: 1.25" Line Tension Capacity: 40 Kips
RL - 1060 K (Standard) RL - 1060 K - SS (Full Stainless Steel)	Max Wire Rope Diameter: 1.25" Line Tension Capacity: 60 Kips
RL - 20175 K (Standard) RL - 20175 K - SS (Full Stainless Steel)	Max Wire Rope Diameter: 2.0" Line Tension Capacity: 175 Kips
RL - 30350 K (Standard) RL - 30350 K - SS (Full Stainless Steel)	Max Wire Rope Diameter: 3.0" Line Tension Capacity: 350 Kips
RL - 40500 K	Max Wire Rope Diameter: 4.0" Line Tension Capacity: 500 Kips
RL - 40800 K (Standard) RL - 40800 K - SS (Full Stainless Steel)	Max Wire Rope Diameter: 4.0" Line Tension Capacity: 800 Kips